


Spherical Roller Bearings



Designation	Principal Dimensions(mm)				Basic Load Ratings(KN)		Limited Speed(rpm)		Weight (kg)
	d	D	B	rs min	Dynamic(Cr)	Static(Cor)	Grease	Oil	
21308	40	90	23	1.5	88	90	3200	4900	0.705
21309	45	100	25	1.5	102	106	2900	4400	0.927
21310	50	110	27	2	118	127	2600	4000	1.21
21311	55	120	29	2	145	163	2400	3700	1.71
21312	60	130	31	2.1	167	191	2200	3400	2.1
21313	65	140	33	2.1	194	228	2000	3100	2.55
21314	70	150	35	2.1	220	262	1900	2900	3.18
21315	75	160	37	2.1	239	287	1800	2700	3.81
21316	80	170	39	2.1	260	315	1700	2500	4.53
21317	85	180	41	3	289	355	1600	2400	5.35
21318	90	190	43	3	320	400	1500	2300	6.3
21319	95	200	45	3	335	420	1400	2100	7.1
21320	100	215	47	3	370	465	1300	2000	8.89
21322	110	240	50	3	495	615	1200	1800	11.2
22205	25	52	18	1	36.5	36	6500	10000	0.186
22206	30	62	20	1	49	49	5700	8800	0.287
22207	35	72	23	1.1	69.5	71	4900	7500	0.446
22208	40	80	23	1.1	79	88.5	4300	6600	0.526
22209	45	85	23	1.1	82.5	95	3800	5900	0.584
22210	50	90	23	1.1	86	102	3500	5300	0.63
22211	55	100	25	1.5	118	144	3200	4900	0.808

Spherical Roller Bearings

22212	60	110	28	1.5	115	147	2900	4500	1.15
22213	65	120	31	1.5	143	179	2700	4200	1.5
22214	70	125	31	1.5	154	201	2500	3900	1.55
22215	75	130	31	1.5	166	223	2300	3600	1.65
22216	80	140	33	2	213	277	2200	3400	1.99
22217	85	150	36	2	251	320	2100	3200	2.49
22218	90	160	40	2	292	385	1900	3000	3.24
22219	95	170	43	2.1	294	390	1800	2800	4.1
22220	100	180	46	2.1	315	415	1700	2700	4.95